

Simple[®]

KEY SWITCH

Key switch is a kind of security device, which is used for roller shutters, shutter doors, industrial doors etc.



16018-4A

For more information
Please visit our website: www.China-develop.com

PRODUCT INFORMATION



16018-1A L7.2*W8.1*H7.2cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-1B L7.2*W8.1*H9cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 32A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-1C L10*W11.2*H7.2cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-2A L8.5*W8.5*H4.2cm

Description:

- Aluminum alloy material, Zinc-alloy cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-81 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-2B L8.5*W8.5*H4.8cm

Description:

- Aluminum alloy material, Zinc-alloy cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-81 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-3A L7.4*W7.4*H4.6cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Aluminum oxide plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-3B L7.4*W7.4*H4.6cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-3C L10.5*W10.4*H4.8cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Aluminum oxide plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-3D L10.5*W10.4*H4.8cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Stainless steel plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-4A L10.8*W11.2*H6.8cm

Description:

- Aluminum alloy material, Brass cylinder
- Brass keys, Aluminum alloy plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: DC500V 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-4B L10.8*W11.2*H6.8cm

Description:

- Aluminum alloy material, Brass cylinder
- Brass keys, Aluminum alloy plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: DC500V 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-5A L12.2*W15*H7.5cm

Description:

- Aluminum alloy & galvanvanized iron material, Brass cylinder
- Brass keys, Aluminum alloy plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: DC500V 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-5B L12.2*W15*H7.5cm

Description:

- Aluminum alloy & galvanvanized iron material, Brass cylinder
- Brass keys, Aluminum alloy plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: DC500V 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-7A L7.4*W7.4*H6cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal keys, Aluminum oxide plate
- Silver plated contacts and terminals
- 1-1000 combinations available
- Rated Load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-8 L10.8*W9.5*H5.9cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal Keys
- Silver plated contacts and terminals
- 1-500 combinations available
- Rated load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-9 L11*W9.6*H6.1cm

Description:

- Zinc alloy material, Brass cylinder
- Metal Keys
- Silver plated contacts and terminals
- 1-500 combinations available
- Rated load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-10 L7*W7*H4.5cm

Description:

- ABS material, Brass cylinder
- Metal Keys
- Silver plated contacts and terminals
- 1-500 combinations available
- Rated load: Maximum operating current: 16A
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding



16018-11 L10.5*W8.2*H4.4cm

Description:

- Aluminum alloy material, Brass cylinder
- Metal Keys Aluminum oxide plate
- Silver plated contacts and terminals
- 1-500 combinations available
- Rated load: 5A AC250V, 10A AC125V
- Insulation Resistance: 100MΩMin
- Dielectric Strength: 1500VAC (50-60HZ)
- Terminals and Grounding